



**Chicago
Pneumatic**

Tools Renewed Inc
Tel: 800-247-3639
Fax: 865-665-9821
Email: sales@toolsrenewed.com

Vibrators

Chicago Pneumatic is proud to introduce a new line of Concrete Vibrators. The CP-1150, CP-2190 and CP-3250 are heavy duty tools designed for pours of low slump concrete in columns, footings, slabs and walls. Each tool has a greater radius of influence which translates to more work accomplished in a shorter period of time. And, unlike electric concrete vibrators, there is no chance of shock or need for extension cords and plugs.

Features:

- Three head diameters to choose from: 1-1/2", 2 1/2" and 3" (38, 62.5 and 75mm)
- Variable speed throttle
- In-line lubricator
- Auxiliary air hose
- Locked motor end plates



CP-1150

All models: 1/2" (12.5mm) NPTF air connection

Catalog Number	Part Number	Radius of Influence mm (in.)	Capacity l/s	Vibration per minute	Head Dimensions		Net Weight kg (lb.)	Length w/o Aux. hose mm (in.)	C.F.M Average
					Diameter mm (in.)	Length mm (in.)			
CP-1150	T022138	228.6-254.0 (9 - 10)	319	10,000	38.1 (1 1/2)	457.2 (18)	7.3 (16)	2184.4 (86)	28
CP-2190	T019308	381.0-406.4 (15 - 16)	700	12,000	36.5 (2 1/2)	349.3 (13 3/4)	12.3 (27)	2997.2 (118)	65
CP-3250	T019303	406.4-431.8 (16 - 17)	892	9,000	76.2 (3)	422.4 (16 5/8)	15.9 (35)	2971.8 (117)	85

Chicago Pneumatic is proud to introduce a new Air Powered Cut-Off Saw. The CP-0044 is a powerful tool driven by a direct drive, 4 hp motor and is designed to cut a variety of surfaces including concrete, asphalt and stone. This direct drive saw has no belts to continually check for tension. The CP-0044 is also engineered for precise balance so less effort is needed to do the job at hand. A built-in oiler provides for continuous lubrication so more time is spent on the job and less time servicing. The CP-0044 is also designed with safety in mind using a standard lock-off trigger to help prevent accidental starting. Also the blade guard can be operated with one hand for convenience.

Features:

- Chicago Pneumatic 4 hp motor
- One-hand operation blade guard
- Integral oiler
- Lock-off trigger
- Direct drive operation
- Two position handle



Cut-off Saw

Catalog	Part	Blade Arbor Dia. mm (in.)	No load rpm	Weight with Blade kg (lb)	Overall Length mm (in)	Max. Cutting Depth mm (in)	Blade Cap mm (in)
CP-0044		25.4 (1")	4800	12.7 (28)	673.1 (26 1/2)	101.6 (4")	355.6 (14")